

BESSEN



Besen Charge

Robust and flexible charging cables for use on charging stations or poles with type 2 outlet. With charging effects from 3,7 kW (16A 1-phase) to 22 kW (32A 3-phase), Besen Charge offers support for all common charging effects. The coiled cable ensures that the cable does not make contact with the ground and avoids dirty cables in the car. The cables have high ingress and impact protection, as well as active temperature monitoring.



Type 2 (IEC-62196)



Type 1 (SAE J1772)

Model	BS-CHC001-S	BS-CHC002-S	BS-CHC003-S	BS-CHC004-S	BS-CHC007-S	BS-CHC008-S
Supply plug	Type 2 (IEC-62196)				Type 2 (IEC-62196)	
Car plug	Type 2 (IEC-62196)				Type 1 (SAE J1772)	
Effect	3,7 kW	11 kW	7,4 kW	22 kW	3,7 kW	7,4 kW
Current	16A		32A		16A	32A
Phases	1-fas	3-fas	1-fas	3-fas	1-fas	1-fas
Ingress protection	IP 66				IP 66	
Impact protection	IK 10				IK 10	
Fire rating	UL94				UL94	
Protection	Temperature monitoring				Temperature monitoring	
Certification	CE				CE	
Operating temp	-40 til +100C				-40 til +100C	
Cable material	TPU				TPU	

